

# BOMBA 20 A1

Access 1 enclosure

MDF vented box, 16mm (5/8") thick, internal damping material  
More rigidity, less vibrations

NBR surround  
Excellent reliability



Streamlined port  
No chuffing noise

50mm (2") voice coil  
High power handling

20cm (8") subwoofer, all weather woven glass fiber cone  
Dynamic bass, humidity resistant

Numerous settings available, including:

- High and low level (4V compatible) inputs  
More wiring possibilities : line output or speaker output of the car radio
- Adjustable Bass Boost level (0/+18dB at 45Hz)  
Vented box which entirely fits to the several listening tastes
- Adjustable cut-off frequencies (50-200Hz ; 12dB/oct),  
0-180° phase selector  
Optimized coupling with the loudspeakers installed in the car

Type	Active vented box 20cm (8") subwoofer
Max. power	250W
Internal amplifier	125W Rms
Frequency response	46Hz - 500Hz
Height	250mm (9.13/16")
Base depth	340mm (13.3/8")
Length	392mm (15.7/16")

## It makes the difference:

- 2 in 1 product (vented box + amplifier): the qualitative and economical solution.
- Amplifier specially designed for the subwoofer.
- Extremely compact vented box for an easy integration.
- The Focal sound.

