

130 VR

Polyglass kit

- Polyglass cone
Neutral sound without coloration
- Butyl surround
Resilient material, promoting long life
- 32mm Kapton® voice-coil former
High power handling
- Zamak chassis
Strong rigid and non-magnetic chassis
- Voice-coil cooling system
Optimum reliability, performance consistency
- "Diamond cutting" aluminum protection cover
More aesthetic
- Adjustable tweeter level
Level setting according to tweeter location
- Polypropylene capacitor
Neutral reproduction of high frequencies
- Air core inductor with a low serial resistance
Insensitive to parasite
- Real 12/12dB/octave crossover
Optimum coupling of woofer and tweeter



- TNB inverted dome tweeter
Detailed and non directive
- Double push-pull Neodymium magnet
High linear tweeter
- Voice coil on aluminum former
High dissipation characteristics

Technical characteristics:

130mm (5") woofer
32mm (1.26") voice-coil
90mm (3.54") magnet
Inverted TNB dome
2 way separate crossover 12/12 dB (4kHz)
Adjustable tweeter level: 0, -3, -6 dB
Max. power: 100W
Nom. power: 50W
Sensitivity (2.83V/1m): 94 dB
Frequency response: 80hz – 28kHz
Grilles supplied

It makes the difference:

- High Sensitivity
- Kit dedicated to Hi-Power car radio, no amplifier needed
- All Focal technologies from the beginning of the range

