

165 VR

High sensitivity Polyglass kit

- Polyglass cone
Neutral sound without coloration
- 32mm (1-1/4") voice coil on Kapton® former
High power handling
- Zamak basket
Strong rigid chassis, non-magnetic, non-resonant
- 90mm (3-9/16") magnet
High sensitivity for more dynamic (94.5 dB)
- 6-6dB or 12-12 dB crossover slope selector
Optimization of the integration of the speakers for all the vehicles and locations
- Adjustable tweeter level
Tweeter level according to location
- Air core inductor with a low serial resistance
Insensitive to parasite



- Aluminum/magnesium inverted dome TNB tweeter
Smooth and detailed treble
- Neodymium push-pull magnet
High linearity tweeter
- Ferrofluided voice coil on aluminum former
Excellent heat dissipation characteristic

165mm (6-1/2") woofer,
32mm (1-1/4") voice coil,
90mm (3-9/16") magnet,
45mm (1-3/4") tweeter,
Aluminum/magnesium inverted dome tweeter
6-6 dB or 12-12 dB/octave 2-way crossover
(3.5kHz at 6dB/oct. ; 4.2kHz at 12dB/oct.),
Adjustable slope of the woofer (6 or 12dB/oct.),
Adjustable tweeter level (-2, 0, +2dB)
Max. power: 150W
Nom. power: 75W
Sensitivity (2.83V/1m): 94.5dB
Frequency response: 80Hz – 28kHz
Accessories: grilles and tweeter supports
(surface and flush mounting) supplied

It makes the difference:

- Very high-fidelity sound reproduction
- Outstanding dynamic (94.5dB) for true sensations
- Wide sound stage, deep and precise at the source of musical emotion
- Adjustment of the crossover slope for a perfect integration
- The emblematic reference in the Polyglass line

